



INNOVATIVE SOLUTIONS FOR CRITICAL ENVIRONMENTS

Valutek, Inc

220 South 9th St.

Phoenix, Arizona, 85034, United States

P +1 602.256.0540 | F +1 602.252.1972

valutek.com | quality@valutek.com

CERTIFICATE OF ANALYSIS

Part Number:	VTPNWLS-1818
Product Type:	Polyester Wiper
Edge Treatment:	Laser Sealed
Lot Number:	240625-100948
Sample Received Date:	06-30-2024
Manufacturing Date:	06-25-2024
Test Date:	07-05-2024

Page 1 of 2

Physical Properties

Test	Method	Specification	Actual	Result
Dimensions	Tape Measure	18" x 18" ($\pm 0.5"$)	18 x 18	Pass
Basic Weight	TAPPI T-410	135 $\pm$ 5 g/m ²	136	Pass

Absorbency

Test	Method	Specification	Actual	Result
Sorptive Efficiency	IENT-RP.CC004.3	Min. 2 ml/g	2.2	Pass
Sorptive Capacity	IENT-RP.CC004.3	Min. 310 ml/m ²	353	Pass
Sorptive Rate	IENT-RP.CC004.3	< 1 sec	0.5	Pass

Cleanliness

Test	Method	Specification	Actual	Result
LPC ($\geq 0.5\mu\text{m}$)	IENT-RP.CC004.3	< 10 x 10 ⁶ particles/m ²	9.73	Pass
TNVR - IPA	IENT-RP.CC004.3	Max. 0.1 g/m ²	0.070	Pass
TNVR – DI H2O	IENT-RP.CC004.3	Max. 0.02 g/m ²	0.006	Pass

Extractables

Test Method: IEST-RP.CC004.3

Ions	Specification	Actual	Result
Sodium	Max. 0.2 ppm	0.015	Pass
Potassium	Max. 0.2 ppm	0.026	Pass
Calcium	Max. 0.5 ppm	0.019	Pass
Magnesium	Max. 0.2 ppm	0.048	Pass
Ammonium	Max. 0.3 ppm	0.049	Pass
Nitrate	Max. 0.3 ppm	0.024	Pass
Fluoride	Max. 0.2 ppm	0.010	Pass
Nitrite	Max. 0.2 ppm	ND	Pass
Bromide	Max. 0.2 ppm	0.027	Pass
Phosphate	Max. 0.3 ppm	ND	Pass
Chloride	Max. 0.2 ppm	0.036	Pass
Sulphate	Max. 0.2 ppm	0.078	Pass

Fourier Transform Infra-Red Test

FTIR	Method	Specification	Actual	Result
Silicone, Amide & DOP	IEST-RP.CC004-3	Absent	Absent	Pass

Notes:



Tested by:
Renugaa Krishnan
 Laboratory Coordinator



Approved by:
Vijendraan Venkitasalam
 Quality Manager